Characteristic features EN 1307

Name of article

Method of production ISO 2424

Width ISO 3018

Surface structure ISO 2424

Colourways

Pile material ISO 2424

Primary backing ISO 2424

Overall weight ISO 8543

Overall thickness ISO 1765

Pile service weight

AT Poodle 1400

Tufted

ca. 50x50

Shag

Uni

100% PA 6.6

PES

ca. 3050 g/m^2

ca. 11,5 mm

ca. 1400 g/m^2

Secondary backing ISO 2424

Electrostatic loading ISO 6356

Surface resistivity ISO 10965 ROT

Transparency to heat ISO 8302

Light fastness ISO 105-B02 Water fastness EN ISO 105 E01

Friction fastness EN ISO 105-X12

Stitch rate ISO 1763

Welltex® Acoustic

< 2 KV

 $10^9 \Omega$

 $0.09 \, K^* m^2 / W$

> 5

> 4

> 3-4

ca. $51.000/m^2$































EN 14041 | DOP: 1060-OC-3497 CPR: 1658-CPR-3497 | NB: 1658

Health-promoting properties AIR



- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers



70 710 3720-8





Health-promoting ACOUSTIC properties



- High acoustic effectiveness as standard
- Improved impact sound insulation +31dB Enhanced room acoustics $+0.4\alpha$
- 1000 Hz 125 250 500 2000 4000 0,10 0,40 0,50 0,05 0,50 0,65
- Increased employee concentration and motivation through enhanced well-being

Environmental properties

98547C8F

- Completely recyclable
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- · Easy cleaning with water only


















Product Information

AT POODLE - The carpet presents itself with a velour construction, featuring a shimmering surface of elegant appearance. The choice of color has a decisive impact on the visibility of the tiles as well as the maintenance effort. The lighter the color choice, the more delicate it can be.

Installation Instructions

Great attention is placed on laying the tiles in a harmonious alignment, thus creating a coherent overall image. At the same time, care is taken not to trap the pile - that is, the yarn ends at the seams, in order to preserve both the aesthetic quality and the lasting functionality of the carpet.



Data status 10.06.2025. Subject to changes due to technical advancements.

